



STAFF PAGING

Developing robustness The RX-AP2




NOW AVAILABLE

From the ground up,
we introduce the RX-AP2 as **THE
Staff Pager of the Year.**
Designed to take your team
communication to the next level.



Quickly inform
and direct staff



Optimize
Your Labor



Shorten
Response Time

IMPROVEMENTS

New Color Display

Support for special characters,
easily readable font sizes, configurable
background lighting and font color.

New Charge Status Light

For the first time in a Staff Pager, there is an
LED to display the charging status.
So your employees know whether the device
is charged at the start of each shift.

New Li-Ion battery

The new AP2 has a significantly longer
lifespan due to its automatic
deep discharge protection.

New housing material

Composed of individual fibers,
the advanced casing of the new AP2
provides far greater robustness.





STAFF PAGING

Specs & Transmitter

Dimensions (Device)

W 7,6cm L 5,7cm H 1,9cm

Weight

65 gr

LI-ION BATTERY (3.7V)

Shock absorption

New charging technology

Dimensions (Display)

W 3,8cm L 2,86cm

3 Button User Interface

Alarming through sound and vibration

Heartbeat Active LED



LRS Connect Transmitter

Integrated in LRS Connect

Up to 9,999 Pagers

LCD Display

Multiple Paging Modes

1x IP-based Ethernet-Connection

1x serial Connection (ascii format)

Dimensions

10,16x 20,5 cm



LRS Interface Transmitter

Interface RS-C232

Integration in many Software-Solutions via USB

(POS, KDS, Logistic-, Patient- and other Software)

1x serial Connection (ascii format)

Dimensions

24,13 x 11,43 x 11,3 cm

