



STAFF PAGING

From Teams - For Teams The new RX-SP6



Redesigned from the ground up for service staff and equipped with powerful enhancements that elevate team communication to a whole new level.

NEW FEATURES & IMPROVEMENTS

New Li-Ion battery

Thanks to automatic deep-discharge protection, the new SP6 offers a significantly longer service life and a runtime of up to 72 hours.

New LED number display


The new digital number display makes over-the-air programming and pager assignment as easy as possible for you.

New housing material


Composed of individual fibers, the enhanced housing of the new SP6 offers far greater robustness.

New Bumper-Ring

For the first time in a staff pager, the SP6 now features our proven bumper ring to better absorb shocks and impacts.



Inform and direct staff faster



Optimize your labor



Optimize response times



Long Range Systems GmbH
Petzvalstraße 56
D - 38104 Braunschweig
MAIL: info@lrseu.com

Your contact person:



STAFF PAGING

Specs & Transmitter

Dimensions

W 7,6cm L 5,7cm H 1,9cm

Weight

64 gr

LI-ION BATTERY (3.7V)

Shock absorption

New DC-Charger

4 Alarm LED's

Belt-Clip (seperate)

Lanyard-Option

Alarm via Beep and Vibration

Heartbeat Active LED



LRS Connect Transmitter

Integrated in LRS Connect

Up to 9,999 Pager

LC-Display

multiple Paging-Modi

1x IP-based Ethernet-Connection

1x serial Connection (ascii format)

Dimensions

10,16 x 20,5 cm



LRS Easy Paging Transmitter

One-Touch-Paging up to Nr. 20

Easy-to-read LC-Display

incl. dry erase name board

multiple Vibration modes

Operates on battery



Long Range Systems GmbH
Petzvalstraße 56
D - 38104 Braunschweig
MAIL: info@lrseu.com

Your contact person: